

DECLARATION OF PERFORMANCE

According to Regulation (EU) No 305/2011 of the European Parliament and of the Council (CPR)

DECLARATION OF PERF. NO.	712-3-20.01 / XXXXXX-XX
PRODUCT	Fire curtain FIBREroll EI, types "A" and "B"
PRODUCT IDENTIFICATION	Serial number XXXXXX-XX (view label on the product)
INTENDED USE	Vertically rolling gate for closing structure openings between adjacent fire compartments
MANUFACTURER	AVAPS s.r.o., U Obalovny 488, 250 67 Klecany, Czech Republic
SYSTEM OF ASSESSMENT	System 1 + System 3
NOTIFIED BODY	Notified body no. 1396 (FIRES s.r.o.)
HARMONISED STANDARDS	EN 16034:2014, EN 13241+A2:2016

EN 16034:2014

The notified body FIRES s.r.o. (NB. 1396) has performed the determination of the product type (declaration of performance of the construction product) on base of type test (including sampling), calculation for the type, table values product description, initial inspection of the manufacturing plant and factory production control plus continuous surveillance, assessment and evaluation of factory production control and issued the Certificate of constancy of product performance no. 1396-CPR-0139.

EN 13241+A2:2016

The notified body FIRES s.r.o. (NB. 1396) has performed assessment and verification of constancy of performance and issued the Assessment and verification of constancy of performance report.

DECLARED PERFORMANCE OF THE PRODUCT:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED STANDARD
Fire resistance	E60, EW60, EI30, EI60 (type "A"), EI245 (type "B")	EN 16034:2014
Smoke control	NPD	
Ability to release	Released	
Self-closing	C	
Durability of ability to release	Release maintained	
Durability of self-closing against degradation	1 ¹⁾	
Durability of self-closing against ageing	Achieved	
Release of dangerous substances:	Product does not release any dangerous substances in excess of the maximum permitted level	EN 13241+A2:2016
Safe opening	Pass	
Mechanical resistance and stability	Pass	

¹⁾ Durability of release according to EN 14637 is 10 000 cycles (report FIRES-MP-012-19-AUNE).

Product characteristics are in compliance with the properties listed in the table. This declaration of performance is made under the sole responsibility of the manufacturer. Signed by and on behalf of the manufacturer:

Klecany, 6.1.2020

Ing. arch. Filip Novotný, CEO