



## **DECLARATION OF PERFORMANCE**

According to Regulation (EU) No 305/2011 of the European Parliament and of the Council (CPR)

DECLARATION OF PERF. NO. 712-6-25.01 / xxxxxx-xx

PRODUCT Fire curtain
FIBREroll EI+

PRODUCT IDENTIFICATION (SN) XXXXXX-XX (view label on the product)

INTENDED USE Vertically rolling gate for closing structure openings between adjacent fire compartments

MANUFACTURER AVAPS s.r.o., U Obalovny 488, 250 67 Klecany, Czech Republic

SYSTEM OF ASSESSMENT System 1 + System 3

NOTIFIED BODY 1396 (FIRES s.r.o.)

HARMONISED STANDARDS EN 16034:2014 + EN 13241+A2:2016

CERTIFICATE NO. 1396-CPR-0225

## **DECLARED PERFORMANCE OF THE PRODUCT:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED STANDARDS
Fire resistance	Subtype 30 - El <sub>2</sub> 30, El <sub>1</sub> 15 Subtype 60 - El <sub>2</sub> 60, El <sub>1</sub> 45 Subtype 90 - El <sub>2</sub> 90, El <sub>1</sub> 60	
Smoke control	NPD	
Ability to release	Released	
Self-closing	С	EN 16034:2014
Durability of ability to release	Release maintained	
Durability of self-closing against degradation	0*	
Durability of self-closing against ageing	Achieved	
Release of dangerous substances	Pass	
Safe opening	Pass	EN 13241+A2:2016
Mechanical resistance and stability	Pass	

<sup>\*</sup> Durability of release according to EN 14637 is 10 000 cycles (report FIRES-MP-012-19-AUNE).

Product characteristics are in compliance with the properties listed in the table. This declaration of performance is made under the sole responsibility of the manufacturer. Signed by and on behalf of the manufacturer:

Klecany, XX.XX.XXXX

Ing. Pavel Novotný, statutory representative