



# DECLARATION OF PERFORMANCE

According to Regulation (EU) No 305/2011 of the European Parliament and of the Council (CPR)

<b>DECLARATION OF PERF. NO.</b>	712-2-25.01 / XXXXXX-XX
<b>PRODUCT</b>	Fire curtain <b>FIBREroll EW</b>
<b>PRODUCT IDENTIFICATION (SN)</b>	XXXXXX-XX (view label on the product)
<b>INTENDED USE</b>	Vertically rolling gate for closing structure openings between adjacent fire compartments
<b>MANUFACTURER</b>	AVAPS s.r.o., U Obalovny 488, 250 67 Klecany, Czech Republic
<b>SYSTEM OF ASSESSMENT</b>	System 1 + System 3
<b>NOTIFIED BODY</b>	1396 (FIRES s.r.o.)
<b>HARMONISED STANDARDS</b>	EN 16034:2014 + EN 13241+A2:2016
<b>CERTIFICATE NO.</b>	1396-CPR-0153

## DECLARED PERFORMANCE OF THE PRODUCT:

ESSENTIAL CHARACTERISTICS		PERFORMANCE	HARMONISED STANDARDS
Fire resistance		up to E180, up to EW180	EN 16034:2014
Smoke control		NPD	
Ability to release		Released	
Self-closing		C	
Durability of ability to release		Release maintained	
Durability of self-closing against degradation		0*	
Durability of self-closing against ageing		Achieved	
Release of dangerous substances		Pass	
Safe opening		Pass	
Mechanical resistance and stability		Pass	

\* Durability of release according to EN 14637 is 10 000 cycles (report FIRES-MP-012-19-AUNE).

Product characteristics are in compliance with the properties listed in the table. This declaration of performance is made under the sole responsibility of the manufacturer. Signed by and on behalf of the manufacturer:

Klecany, XX.XX.XXXX

Ing. Pavel Novotný, statutory representative